

# clover®

**Best Quality, Price, Warranty  
and Customer Service**

**Choose from:**

Hot Cold

Hot Cold Black

Cook Cold

POU Conversation Kit

Hot Cold Mini



**B9A**



**POU  
Conversion**



**B7A**



**B7A  
Black**

# clover®

# Bottled Water Cooler Specifications



## Cabinet

Plastic, high density polyethylene cabinet. Eliminates the problem of rust and corrosion. Superior resistance to UV degradation. One-piece blow molded cabinet is designed to allow easy cleaning and quick cabinet removal for convenient service. Handle on the back of the unit enable easy transport of the water cooler.

## Cold Water Tank

Hygienic silicone on the top of cold water reservoir prevents crawling insects as well as dust and dirt. External copper refrigerant evaporator. Cold water temperature is controlled by an adjustable thermostat.

## Hot Water Tank

Hygienic stainless steel. Highly efficient internal heating element. Non-adjustable thermostat with manual reset safety limiter. Convenient hot water ON/OFF switch. Fireproof insulation.

## Hot Water Thermostat

(Model B7A) Water Temperature is controlled to nearly 185°F (85°C) by automatic ON/OFF switch is easily accessible at the side of cabinet.

## Frame

Two galvanized steel struts ensure cooler stability and impact resistance.



## Specifications

| Model      |            | B7A(Hot & Cold)                                   | B7B(Cook & Cold) |
|------------|------------|---|------------------|
| Cooler     | Weight     | 33.0 lbs(15kg)                                    | 30.8 lbs(14kg)   |
|            | Dimensions | 12.4" (315mm)W x 12.8" (325mm)D x 37.8" (960mm)H  |                  |
| Shipping   | Weight     | 36.3 lbs(16.5kg)                                  | 34.1 lbs(15.5kg) |
|            | Dimensions | 13.2" (335mm)W x 13.8" (350mm)D x 39.4" (1000mm)H |                  |
| Color      |            | White   |                  |
| Electrical |            | 220-240V, 50/60Hz. 100-127V, 50/60Hz.             |                  |

## Cooler Performance

| Room temperature °F(°C) |  | 70° F(21° C) | 80° F(27° C) | 90° F(32° C) |
|-------------------------|--|--------------|--------------|--------------|
| Quantity of cold water  | GPH  | 1.8          | 1.3          | 0.9          |
|                         | 50° F(10° C)served per hour                              | LPH          | 7.0          | 5.2          |
| Quantity of hot water   | GPH  | 2.0          |              |              |
|                         | 185° F(85° C) served per hour<br>(Hot & Cold model only) | LPH          | 7.5          |              |

## Warranty

One year blanket warranty. Three years on the sealed compressor

## Standards

Specifications are subject to the international standards.

## OPTIONS

### Cup Dispenser

- Dimensions : Ø3.3" (84mm) x 13.8" (350mm)H
- Color : Light Gray
- Rim diameter : 2.5" (65mm) ~ 3" (76.2mm)
- Case pack : 20 per case
- Case dimensions  
15" (380mm)W x 19" (480mm)D x 11" (280mm)H



### Hot Water Safety Faucet

Self-closing faucet requires a two-step action that's easy for adults to use, but helps protect small children.  
(US patented)



Specifications are subject to change without notice.